

ON-225

Power by WEICHAI

WP10D238E200

Prime power: 180KW/225KVA

Standby power: 200KW/250KVA

GENERATING POWER SOLUTIONS



Increased availability for new operations

Reliable, robust and versatile generator. Ready to deliver power for a next job.

Increased uptime during operations

Once installed on the end-user-site, the generator will be ready to run: "peace of mind" operation.

Reduced transport and installation costs



The compact and robust design with integrated transport features enables faster and safer transport and installation.

Reduced service & maintenance costs

Longer service intervals. Quicker and more efficient service jobs.

Premium resale value

Designed and built to last.



ONEWPOWER

WWW.ONEWPOWER.COM

DIMENSION		OPEN TYPE	SILENT TYPE
Length (L)	mm	2850	3962
Width (W)	mm	1040	1120
Height (H)	mm	1580	2038
Dry weight	kg	1717	2985
Fuel tank	L	350	500

Technical Data

Model ON-225

Rated prime power	KW	180
Rated standard power	KW	200
Rated voltage line to line	V	380~415
Maximum sound level	dB(@7m)	≤72

Engine

Model	WP10D238E200	
Aspiration	Turbochargine and aftercooled	
Fuel system	mechanical pump	
No. cylinders	6	
Displacement	Liquid	9.726
Bore*Stroke	mm	126*130
Compression ratio	17:1	
Rated speed	r/min	1500
Rated net power(with fan)	Kw	180
Governor type	Electronic	

Exhaust system

Exhaust gas flow	1084kg/h	
Exhaust gas temp	° F (° C)	<700
Max back pressure	6KPA	

Aspiration system

Max inlet pressure	kPa	≤3.5
Combustion volume	L/s	/
Air flow	kg/h	1041

Fuel system

100% load(Prime power)	L/h	51.2
75% load(Prime power)	L/h	37.6
50% load(Prime power)	L/h	25.6
Fuel tank capacity	L	500

Lubrication system

Oil capacity	L	24
Oil consumption	L/H	51.2
Oil pressure	kPa	10
(continuous operation)		

Cooling system

Coolant capacity	L	22
Thermostat operation range	°C	76-88
Max water temperature	°C	98

Alternator

Model	ON-225	
Phase	3	
Voltage	V	380~415
Bearing	1	
Power factor	0.8	
Frequency	Hz	50
Prime power	KW	180
Exciter Type	Brushless, self-excitation	
Voltage regulation	%	±0.5
Protection Grade	IP 23	
Insulation grade	H/H	
Altitude	m	≤1000

Controller

- Model
- Protective functions:
- Low oil pressure
 - High water temperature
 - High/low voltage
 - High Engine Temperature and Overspeed.
 - Voltage regulator frequency regulator
 - Emergency stop
 - Start failure



Control Module Options



- Auto generator control module
- Control module with "Three Remote Control" functions
- ATS auto load transfer screen
- Synchronising control modules
- Power output cabinet

Standard features

- Engine
- Radiator 50°C max, fans are driven by belt
- 24V charge alternator
- Alternator: single bearing alternator IP23, insulation class H/H
- Standard auto control system
- One set of air filter, fuel filter, oil filter
- Main line circuit breaker/MCCB
- Base fuel tank
- Two 24V batteries, rac and cable
- Exhaust system(Ripple flex exhaust pipe, exhaust siphon, flange, muffler)
- User manual

Options

- Battery charge
- Engine heater
- Alternator heater
- PMG
- Water oil separator
- Daily fuel tank
- Remote control panel
- Automatic transfer switch/ATS
- Switch box
- Standard: ● Options: ○

Warranty



WEICHAI ENGINE

12 months from date of purchase and 1000 hours.

Generator

12 months from date of purchase or 1000 hours (whichever occurs first).

Dimensions



ONEWPOWER

ADD: NO . 1 0 7 XIYUAN ROAD , JINAN DISTRICT, FUZHOU CITY, FUJIAN, CHINA

Phone: 15980204507 E-mail: jina@onewpower.com

WWW.ONEWPOWER.COM

