

ON-197

Power by Perkins

1106A-70TAG3

Prime power: 158KW/197KVA

Standby power: 175KW/219KVA

GENERATING POWER SOLUTIONS

Increased availability for new operations

Reliable, robust and versatile generator.
Ready to deliver power for a next job.

Increased uptime during operations

Once installed on the end-user-site, the generator will be ready to run: "peace of mind" operation.

Reduced transport and installation costs



The compact and robust design with integrated transport features enables faster and safer transport and installation.

Reduced service & maintenance costs

Longer service intervals.
Quicker and more efficient service jobs.

Premium resale value

Designed and built to last.



ONEWPOWER

WWW.ONEWPOWER.COM

DIMENSION		OPEN TYPE	SILENT TYPE
Length (L)	mm	2390	3412
Width (W)	mm	1100	1100
Height (H)	mm	1650	1960
Dry weight	kg	2100	2600
Fuel tank	L	350	350

Technical Data

Model ON-197

Rated prime power	KW	158
Rated standard power	KW	175
Rated voltage line to line	V	220~480
Maximun sound level	dB(@7m)	≤72

Engine

Model	1106A-70TAG3	
Aspiration	Turbocharged aftercooled	
Fuel system	mechanical pump	
No. cylinders	6	
Displacement	Liquid	7.01
Bore*Stroke	mm	105*135
Compression ratio	16:01	
Rated speed	r/min	1800
Rated net power(with fan)	Kw	175
Governor type	Mechanical	

Exhaust system

Exhaust gas flow	35.42 m ³ /min	
Exhaust gas temp	° F (° C)	<485
Max back pressure	6 kPa	

Aspiration system

Max inlet pressure	kPa	≤3.5
Combustion volume	L/s	/
Air flow	L/sec	TBA

Fuel system

100% load(Prime power)	L/h	46.4
75% load(Prime power)	L/h	35.3
50% load(Prime power)	L/h	22.7
Fuel tank capacity	L	350

Lubrication system

Oil capacity	L	16.5
Oil consumption	g/kwh	28.3
Oil pressure	kPa	10
(continuous operation)		

Cooling system

Coolant capacity	L	21
Thermostat operation range	°C	76-88
Max water temperature	°C	98

Alternator

Model	ON-197	
Phase	3	
Voltage	V	220~480
Bearing	1	
Power factor	0.8	
Frequency	Hz	60
Prime power	KW	158
Exciter Type	Brushless, self-excitation	
Voltage regulation	%	±1.0
Protection Grade	IP 23	
Insulation grade	H/H	
Altitude	m	≤1000

Controller

- Model
- Protective functions:
- Low oil pressure
 - High water temperature
 - High/low voltage
 - High Engine Temperature and Overspeed.
 - Voltage regulator frequency regulator
 - Emergency stop
 - Start failure



Control Module Options



- Auto generator control module
- Control module with "Three Remote Control" functions
- ATS auto load transfer screen
- Synchronising control modules
- Power output cabinet

